

1. A reflective warning and locating collar for fire hydrants, pylons or support posts, said reflective warning and locating collar comprising:

*Sub C*

a support member having an elongated, flexible, extruded web having a first side and a second side, defined by two parallel longitudinal edges and a first end and a second end, said web having flanges depending from said longitudinal edges of said first side of said web, said flanges terminating with inwardly turned second flanges parallel to said web thereby defining a channel between said web and said inwardly turned second flanges from said first end of said support member to said second end of said support member;

a reflective member comprised of an elongate flexible web slidably receivable and retainable within said channel, said support member and said reflective member having a plurality of alignable apertures proximate their said ends for alignment and receipt of a fastening means so as to permit said support member and said reflective member to be circumscribably engaged about a fire hydrant, pylon or support post forming a reflective warning and locating collar.

*Sub C1  
Ex-Cont.  
cont*

2. The reflective warning and locating collar in accordance with Claim 1 wherein said support member is fabricated from a weather resistant polymer.

3. The reflective warning and locating collar in accordance with Claim 1 wherein said reflective member is bonded to a substrate, said substrate and said reflective member slidably receivable within said channel of said support member.

---

*Ex*

5. A fire hydrant having an identifiability member comprising:

*Sub C1  
cont*

a fire hydrant having a generally vertically tubular member extending upwardly from the ground and in communication with a source of water, a plurality of hose connections extending perpendicularly outwardly from said tubular vertical member, said hose connections having cap members affixed thereto and said tubular vertical member having a cap member affixed to a top end, said cap member incorporating a valve actuator, said identifiability member comprising a reflective warning and locating collar circumscribably engaged about said fire hydrant said reflective warning and locating collar comprising a support member having an elongated, flexible extruded web having a first side and a second side, defined by two parallel longitudinal edges

and a first end and a second end, said web having flanges depending from said longitudinal edges of said first side of said web, said flanges terminating with inwardly turned second flanges parallel to said web thereby defining a channel between said web and said inwardly turned second flanges from said first end of said support member to said second end of said support member, a reflective member comprised of an elongate flexible web slidably receivable and retainable within said channel, said support member and said reflective member having a plurality of alignable apertures proximate their said ends for alignment and receipt of a fastening means so as to permit said support member and said reflective member to be circumscribably engaged about said fire hydrant.

7. The fire hydrant in accordance with Claim 6 wherein said reflective warning and locating collar support member is fabricated from a weather resistant polymer.

8. The fire hydrant in accordance with Claim 6 wherein a second reflective warning and locating collar is positioned about said fire hydrant beneath said extending hose connections.